

Tech Solution Adam Golecky

PeeringDay 2015 Bratislava, 18.3.2015



Follow us







.. and at www.nix.sk / .cz ©






NIX.CZ today


- Neutral platform
- 5 data centers in Prague
- 124 networks
- 42 international
- Daily peak passed 360 Gbps
- Own first duct line between PoP

Entertainment Slide



Foundation of NIX.CZ


- Dual-star topology
- 4x Cisco Nexus 7010
- 6x Cisco Catalyst 6509E
- Fully redundant
- Access to dark fibers
- Route servers



Route servers

- Only BGP traffic through RS
- Data flows directly
- Optional filtering based on BGP communities

Route servers



Route servers

Optional filtering based on BGP communities:

mark for do not advertise pfx to specific ASN


VS

mark for advertise only pfx to specific ASN

RTBH community in FENIX project

Newer access boxes

- "Old" Nexus 7010
- "New" Nexus 7710
- Up to 12x100GE /LC
- Lower power consumption
- Open future to DFA or VPLS




Project FENIX technical requirements



- BCP-38 preventing IP spoofing
- Full redundant connection NIX.CZ
- IPv6
- DNSsec
- Be ready for RTBH
- etc

Time for coffee break



Follow us







.. and at www.nix.sk / .cz ©



